

MOISTURE METER FOR HAY BALES OR CUBES

(SILAGE, FODDER, FORAGE, FEED)

One reader and different sensors for many products



Reader MI-7

- Direct readout.
- With interchangeable sensors.

Sensor SH-6

- Moisture range: 0 to 100%.
- Spread probe of steel of 8 mm and 55 cm in length.

Reader MI-7 characteristics

- Input connector for interchangeable sensors of moisture and temperature.
- Direct readout and automatic correction by temperature.
- Alphanumeric display of 2 lines by 16 characters.
- Range of moisture reading in display: 0 to 100%.
- The version standard includes calibrations for 11 grains (with SH-7 sensor), hay bales or cubes (with SH-6 sensor) and row of hay (with SH-5 sensor).
- Function for standard calibration adjust by means of equalization of the calibration chart.
- Memory of 25 measurements.
- Power battery of 9 volts.
- Dimensions and weight: length overall 19 cm., width 9,5 cm., prof 3,5 cm., weight 300g.

Reader MI-7 optionals

- System of programming of new calibrations for different products. It stores in memory 70 samples.
- PC output and software to store to measurements and calibrations.

MEASURE INSTRUMENTS - Buenos Aires - ARGENTINA

Email: measureinstruments@yahoo.com.ar

Web: www.measureinstruments.com.ar