

GRAIN MOISTURE METER

(Grains, cereals, flour, powder, granulated)

One reader and different sensors for many products



Sensor SH-7

- The amount of necessary sample is by weight and not by volume.

Reader MI-7

- Direct readout.
- Interchangeable sensors.
- Option of programming for other products.

Characteristics of reader MI-7

- Input connector for the interchangeable sensors of moisture and temperature.
- Direct readout and automatic correction of the measurement by temperature.
- Alphanumeric display of 2 lines by 16 characters.
- Moisture range reading in display: 0 to 100%.
- The standard version includes calibrations for 11 grains (maize, soybean, sunflower, wheat, white wheat, sorghum, rice with husk, oats, rye, barley, linen), hay bales, and hay row.
- Function of adjustment of the calibrations standard, by means of equalization of the calibration chart.
- Store in memory last the 25 measurements.
- Power: battery of 9 volts.
- Dimensions and weight: length overall 19 cm., width 9,5 cm., prof. 5 cm., weight 300g.

Optionals

- System of programming of calibrations for different products. (Grain, granulated, flours, dusts)
- Store in memory 70 samples patterns.
- Output for computer and software to store measurements and calibrations.

MEASURE INSTRUMENTS - Buenos Aires - ARGENTINA

Email: measureinstruments@yahoo.com.ar

Web: www.measureinstruments.com.ar